

PROTAC® RAIL MOUNT HL-X LASER MULTI-FUEL. HIGH LUMEN LONG GUN LIGHT WITH INTEGRATED RED LASER







MULTI-FUEL: Uses Streamlight rechargeable 18650 USB lithium battery; also accepts two CR123A lithium batteries

Includes remote rail grabber, remote pressure switch, push-button tailcap switch, remote retaining clips, double-sided tape and zip ties

Material/Lens 6000 Series machined aircraft aluminum with anodized finish. High temperature, shock mounted, AR coated, impact resistant Boro Float glass.

Dims/Weight Length: 6.56 in. (16.7 cm); Width: 1.47 in. (3.73 cm); Height: 1.76 in. (4.47 cm)

10.3 oz (292.0 grams) with CR123A batteries 10.8 oz (306.2 grams) with 18650 Li Ion rechargeable battery

White LED technology, impervious to shock with a 50,000 hour lifetime; TIR optic produces a concentrated beam with optimum peripheral Light Source illumination.

Output/Runtime

- TEN-TAP® Programming: Choice of three operating modes: 1.) high/strobe; 2.) high only; 3.) low/high
- High for maximum illumination: 1,000 lumens; 18,200 candela; 270m beam; runs 1.25 hours (CR123A batteries); runs 1.5 hours (18650 battery)
- Low for extended run time: 60 lumens; 1,100 candela; 66m beam; runs 20 hours (CR123A batteries); runs 23 hours (18650 battery)
- Strobe for signaling or disorienting: runs 2.25 hours (CR123A batteries); runs 3.25 hours (18650 battery)

Switch Multi-function, push-button tactical tail switch or Dual remote pressure switch with latching push button. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: 1.) high/strobe; 2.) high only; 3.) low/high

Battery Uses two CR123A lithium batteries or one Streamlight 18650 lithium ion battery.

Features

- Remote pressure switch features momentary and "constant on" operation Mounts directly to guns with MIL-STD-1913 (Picatinny) rails
- One handed on/off & tighten interface keeps hands away from muzzle when attaching/detaching.
- Unique clamp design allows Windage and Elevation screws to be in the proper orientation for laser sighting in any mounted position
- Operating temperature: -20°F to +120°F
- IPX4 water-resistant
- Serialized for positive identification

Meets applicable European Community Directives. Approvals

Warranty

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Item	UPC	Part #
ProTac Rail Mount HL-X Laser with lithium batteries - Box	080926-88066-5	88089
ProTac Rail Mount HL-X Laser USB with 18650 USB battery - Box	080926-88071-9	88090









Item	UPC	Part #
18650 Battery Charge Cradle	080926-22100-0	22100
18650 Charger Kit - USB (includes two 18650 USB batteries)	080926-22010-2	22010
18650 Charger Kit - 120V AC (includes two 18650 USB batteries)	080926-22011-9	22011
18650 USB Battery	080926-22101-7	22101
18650 USB Battery - 2pk	080926-22102-4	22102
Lithium Batteries 2 Pack	080926-85175-7	85175
Lithium Batteries 12 Pack	080926-85177-1	85177
Lithium Batteries 400 Pack	080926-85179-5	85179
Lithium Batteries 6 Pack	080926-85180-1	85180
Remote Retaining Clip	080926-88178-5	88178

Made in China